

Xprinter®



Mobile Label printer

XP-P324B




- Support charging by USB
- LCD screen, easy to operate
- 2500 mAh large capacity battery, long standby
- MAX 70 mm / sec low noise, high speed printing
- Support Windows system, Android system, IOS system



XP-P324B

Mobile Label Printer



Printing		XP-P324B
Resolution		203 DPI
Printing method		Direct Thermal
Max.print speed		Max. 70mm (2.7") / s
Max.print width		72 mm (2.8")
Max.print length		1778 mm (70")
Media		
Media type		Continuous, gap, black mark
Media width		20 mm ~ 76 mm
Media thickness		0.06 mm ~0.254 mm
Media core diameter		25.4 ~ 76.2 mm (1" ~ 3")
Performance Features		
Processor		32-bit CPU
Memory		8MB Flash Memory/ 8MB SDRAM
Interface		Standard version: USB+Bluetooth Optional:USB+WIFI
Screen		OLED (1.3") Resolution:128*64 pix
Sensors		①Gap sensor ②Cover opening sensor ③Black mark sensor
Performance Features		
Internal fonts		8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code		Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code		PDF-417, Maxicode, DataMatrix, QR code,Aztec
Rotation		0°、90°、180°、270°
Emulaion		TSPL、EPL、ZPL、DPL、CPCL、ESC/POS
Physical Features		
Dimensions		136 mm (L) x 112 mm (W) x 63 mm (H)
Weight		357 g
Reliability		
Printer head life		30 KM
Software		
Operation system		Windows / Android / iOS
SDK		Windows / Android / iOS
Power supply		
Output		DC 9V/2A
Battery life		7.4V/2500mAh
Environmental Conditions		
Operation environment		5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment		-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

